



**NON-RESIDENTIAL EXISTING BUILDING
(NREB): RESORT**

VERSION 1.0 | FEBRUARY 2014

www.greenbuildingindex.org | info@greenbuildingindex.org

GREENBUILDINGINDEX SDN BHD (845666-V)

A-12-13A Menara UOA Bangsar, 5 Jalan Bangsar Utama 1, 59000 Kuala Lumpur, Malaysia Tel 603 2283 2566 Fax 603 2284 2566

CONTENTS

PAGE 2	ACKNOWLEDGEMENT AND COPYRIGHT
	INTRODUCTION
PAGE 3	What is the Green Building Index (GBI)?
PAGE 3	Who can use the Green Building Index (Non-Residential)?
PAGE 4	PROJECT INFORMATION
PAGE 5	CONSULTANTS INFORMATION
	ASSESSMENT CRITERIA
PAGE 6	Summary of Final Score
PAGE 6	Green Building Index Classification
PAGE 7	Summary of Contents
	INDIVIDUAL ITEM SCORE
PAGE 9	PART 1: Energy Efficiency (EE)
PAGE 11	PART 2: Indoor Environmental Quality (EQ)
PAGE 14	PART 3: Sustainable Site Planning & Management (SM)
PAGE 15	PART 4: Materials & Resources (MR)
PAGE 16	PART 5: Water Efficiency (WE)
PAGE 17	PART 6: Innovation (IN)

ACKNOWLEDGEMENT AND COPYRIGHT

The Green Building Index has been developed by PAM and ACEM for the purposes as mentioned herein and may be subject to further updating and/or modification in future.

The Green Building Index (GBI) is based upon the existing international rating tools such as the Singapore Green Mark and the Australian Green Star system, amongst others which have been extensively modified for the Malaysian application. Grateful acknowledgment is made to the owners of copyright for these systems for use of their documents, information and materials in the development of the GBI.

While every care has been taken by PAM and ACEM in the development of the GBI to establish and acknowledge copyright of the information and materials used, and contact the copyright owners known to PAM/ACEM, PAM and ACEM tender their apologies for any accidental copyright infringement.

The GBI is a copyright of PAM and ACEM in which PAM and ACEM reserve all rights. No part of the GBI may be used, modified, reproduced, stored in a retrieval system or transmitted in any form, or by any means, electronic, mechanical, photocopying, recording or otherwise, without the prior written permission of PAM and ACEM.

DISCLAIMERS

PAM and ACEM shall not be held liable for any improper or incorrect use of the GBI (inclusive of the materials and/or information contained therein) and assume no responsibility for any user's use of it. In no event shall PAM and ACEM be liable for any damages whatsoever, whether direct, indirect, incidental, special, exemplary or consequential (including, but not limited to business interruption or loss of use, data or profits) regardless of cause, and on any basis of liability, whether in contract, strict liability or tort (including negligence, misrepresentation or otherwise) arising in any way out of the use of the GBI or the information and materials contained therein.

The information and materials in the GBI are provided "as is" and without warranties of any kind expressed or implied. PAM and ACEM do not warrant or make representations as to the accuracy and completeness of any information and/or materials contained therein. While every effort has been made to check the accuracy and completeness of the information and materials given, the users should always make their own relevant checks. Accordingly, PAM and ACEM do not accept responsibility and liability for misstatements made in it or misunderstanding from it.

The GBI is no substitute for professional advice. Users are advised to consult with appropriate and accredited professional advisors for advice concerning specific matters pertaining to the GBI before adopting or using it. PAM and ACEM disclaim any responsibility for positions taken by users in their individual cases or for any misunderstandings and losses, direct or indirectly, on the part of the users.

PAM and ACEM do not endorse or otherwise acknowledge the GBI rating achieved by the use of the GBI. PAM and ACEM offer a formal certification process for ratings; which service provides for independent third party review of points claimed to ensure that all credits can be demonstrated to be achieved by the provision of the necessary documentary evidence. Use of the GBI without formal certification by PAM and ACEM does not entitle the user or any other party to promote the achieved GBI rating. Notwithstanding the above, neither the GBI formalization nor any certification issued by PAM and ACEM shall be used for advertising or product/services endorsement purposes.

INDEMNIFICATION

To the extent permitted by applicable law, by using the GBI, the user agrees to defend, indemnify, and hold harmless, PAM and ACEM, their officers, employees, members, representatives and agents from and against all claims and expenses of whatsoever kind and amount, arising out of the user's use of the GBI or materials and information contained therein and not to pursue any cause of action whatsoever against PAM and ACEM under any conceivable circumstances.

INTRODUCTION

WHAT IS THE GREEN BUILDING INDEX (GBI)?

The Green Building Index is an environmental rating system for buildings developed by PAM (Pertubuhan Arkitek Malaysia / Malaysian Institute of Architects) and ACEM (the Association of Consulting Engineers Malaysia). The Green Building Index is Malaysia's first comprehensive rating system for evaluating the environmental design and performance of Malaysian buildings based on the six (6) main criterias of Energy Efficiency, Indoor Environment Quality, Sustainable Site Planning & Management, Materials & Resources, Water Efficiency, and Innovation.

The Green Building Index is fundamentally derived from existing international rating tools, including the Singapore Green Mark and the Australian Green Star system, but extensively modified for relevance to the Malaysian tropical weather, environmental context, cultural and social needs.

This PAM/ACEM GBI initiative aims to assist the building industry in its march towards sustainable development. The GBI environmental rating system is created to:

- **Define green building by establishing a common language and standard of measurement;**
- **Promote integrated, whole-building design;**
- **Recognise and reward environmental leadership;**
- **Transform the built environment to reduce the environmental impact of development; and**
- **Ensure new buildings remain relevant in the future and existing buildings are refurbished and thereafter sustained properly to remain relevant.**

WHO CAN USE THE GREEN BUILDING INDEX (NON-RESIDENTIAL)?

PAM/ACEM encourage all members of Project Teams, Building owners, Developers and other interested parties (including Contractors, Government and Design and Build Contractors) to use the Green Building Index to validate environmental initiatives of the design phase of new non-residential construction or base non-residential building refurbishment; or construction and procurement phase of non-residential buildings. Use of the Green Building Index is encouraged on all such projects to assess and improve their environmental attributes.

Use of the Green Building Index (Non-Residential) tool without formal certification by an independent accredited GBI Certifier does not entitle the user or any other party to promote the Green Building Index rating achieved. No fee is payable to PAM/ACEM for such use, however formal recognition of the Green Building Index rating - and the right to promote same - requires undertaking the formal certification process offered by PAM/ACEM.

Whilst GBI NREB is a generic rating tool for Office Buildings, GBI NREB: RESORT is a bespoke rating tool developed for Resort Hotels.

All Green Building Index rating tools are reviewed annually; please forward any feedback to info@pam.org.my.

PROJECT INFORMATION

PROJECT NAME		
PROJECT REGISTRATION NO.		
PROJECT ADDRESS		
	<small>POSTCODE</small>	<small>STATE</small>
CONSTRUCTION TYPE		
TOTAL GROSS FLOOR AREA (GFA)		
LAND AREA (FOR LANDED PROPERTY)		
REGISTRATION FEE (EXCLUDING GST)		
TARGETTED RATING		
TOTAL POINTS CLAIM		
EXPECTED CONSTRUCTION DATE	<small>COMMENCED</small>	<small>COMPLETION</small>
DATE BUILDING COMPLETED (NREB/IEB ONLY)		
PROJECT DESCRIPTION & MAJOR DESIGN FEATURES		

CONSULTANTS INFORMATION

OWNER'S NAME		
COMPANY		
OWNER'S REPRESENTATIVE	NAME	DESIGNATION

ARCHITECT	NAME	PROFESSIONAL REG. NO.	COMPANY
CIVIL ENGINEER	NAME	PROFESSIONAL REG. NO.	COMPANY
STRUCTURAL ENGINEER	NAME	PROFESSIONAL REG. NO.	COMPANY
MECHANICAL ENGINEER	NAME	PROFESSIONAL REG. NO.	COMPANY
ELECTRICAL ENGINEER	NAME	PROFESSIONAL REG. NO.	COMPANY
QUANTITY SURVEYOR	NAME	PROFESSIONAL REG. NO.	COMPANY
LAND SURVEYOR	NAME	PROFESSIONAL REG. NO.	COMPANY
LANDSCAPE ARCHITECT	NAME	PROFESSIONAL REG. NO.	COMPANY
COMMISSIONING SPECIALIST (CxS)	NAME	PROFESSIONAL REG. NO.	COMPANY
GBI FACILITATOR	NAME	PROFESSIONAL REG. NO.	COMPANY
OTHER SPECIALIST CONSULTANT(S)			
MAIN CONTRACTOR			
LOCAL AUTHORITY			

DETAIL ASSESSMENT CRITERIA SUMMARY OF FINAL SCORE

PART	ITEM	MAXIMUM POINTS	SCORE
1	Energy Efficiency (EE)	38	
2	Indoor Environmental Quality (EQ)	16	
3	Sustainable Site Planning & Management (SM)	10	
4	Material & Resources (MR)	9	
5	Water Efficiency (WE)	14	
6	Innovation (IN)	13	
TOTAL SCORE		100	

GREEN BUILDING INDEX CLASSIFICATION:

POINTS	GBI RATING
86 to 100 points	Platinum
76 to 85 points	Gold
66 to 75 points	Silver
50 to 65 points	Certified

DETAIL ASSESSMENT CRITERIA

SUMMARY OF CONTENTS

PART	CRITERIA	ASSESSMENT CRITERIA	POINTS	TOTAL
	EE	ENERGY EFFICIENCY		
1	Design & Performance			38
	EE1	Minimum EE Performance	2	
	EE2	Lighting Zoning	3	
	EE3	Electrical Sub-metering	2	
	EE4	Renewable Energy	5	
	EE5	Advanced or Improved EE Performance - BEI	15	
	Commissioning			
	EE6	Enhanced or Re-commissioning	4	
	EE7	On-going Post Occupancy Commissioning	2	
	Monitoring, Improvement & Maintenance			
EE8	EE Monitoring & Improvement	2		
EE9	Sustainable Maintenance	3		
	EQ	INDOOR ENVIRONMENTAL QUALITY		
2	Air Quality			16
	EQ1	Minimum IAQ Performance	1	
	EQ2	Environmental Tobacco Smoke (ETS) Control	1	
	EQ3	Indoor Air Pollutants	2	
	EQ4	Mould Prevention	1	
	Thermal Comfort			
	EQ5	Air Movement	1	
	EQ6	Thermal Comfort: Controllability of Systems	2	
	Lighting, Visual & Acoustic Comfort			
	EQ7	Daylighting	2	
	EQ8	Electric Lighting Levels	1	
	EQ9	High Frequency Ballasts	1	
	EQ10	Internal Noise Levels	1	
	Verification			
EQ11	IAQ Before/During Occupancy	1		
EQ12	Occupancy Comfort Survey: Verification	2		
	SM	SUSTAINABLE SITE PLANNING & MANAGEMENT		
3	Facility Management			10
	SM1	GBI Rated Design & Construction	1	
	SM2	Building Exterior Management	1	
	SM3	Integrated Pest Management, Erosion Control & Landscape Mgt	1	
	Transportation			
	SM4	Resort Guests Transportation - Green Vehicle	1	
	SM5	Staff Mobility - Provision of non motorised transportation	1	
	Reduce Heat Island Effect			
SM6	Greenery & Roof	4		
SM7	Building User Manual	1		

DETAIL ASSESSMENT CRITERIA

SUMMARY OF CONTENTS (CONTINUED)

PART	CRITERIA	ASSESSMENT CRITERIA	POINTS	TOTAL	
4	MR	MATERIALS & RESOURCES		9	
	Reused & Recycled Materials				
	MR1	Material Reuse and Selection	1		
	MR2	Recycle Content Materials	1		
	Sustainable Materials & Resources and Policy				
	MR3	Sustainable Timber	1		
	MR4	Sustainable Purchasing Policy	1		
	Waste Management				
	MR5	Storage, Collection & Disposal of recyclables	3		
Green Products					
	MR6	Refrigerants & Clean Agents	2		
5	WE	WATER EFFICIENCY		14	
	Water Harvesting & Recycling				
	WE1	Rainwater Harvesting	4		
	WE2	Water Recycling	3		
	Increased Efficiency				
	WE3	Water Efficient - Irrigation/Landscaping	2		
	WE4	Water Efficient Fittings	3		
	WE5	Metering & Leak Detection System	2		
6	IN	INNOVATION		13	
	IN1	Innovation & Environmental Initiatives	12		
	IN2	Green Building Index Facilitator	1		
			TOTAL POINTS	100	

1

ENERGY EFFICIENCY (EE)

DESIGN & PERFORMANCE | COMMISSIONING | MONITORING, IMPROVEMENT & MAINTENANCE

38 POINTS

ITEM	AREA OF ASSESSMENT	DETAIL POINTS ALLOCATED	MAX POINTS	SCORE
DESIGN & PERFORMANCE				
EE1	MINIMUM EE PERFORMANCE (MANDATORY COMPLIANCE)			
	Building envelope and installations to achieve minimum energy efficiency (EE) performance so as to reduce energy consumption in buildings, thus reducing CO ₂ emission to the atmosphere. Building Envelope to meet the following minimum EE requirements as stipulated in MS 1525:		2	
	a. OTTV ≤ 50, RTTV ≤ 25, Roof U-Value ≤ 0.4 (Light weight) or ≤ 0.6 (Heavy weight). Submit calculations (use of the BEIT software or other GBI approved software is acceptable), AND	1		
	b. Provision of Energy Management Control system where Air-conditioned space ≥ 4000 m ² .	1		
EE2	LIGHTING ZONING			
	Provide flexible lighting controls to optimise energy savings:-		3	
	All individual or enclosed spaces to be individually switched; and the size of individually switched lighting zones shall not exceed 30m ² ; with switching clearly labelled and easily accessible. Guestrooms to be provided with multi-light switches.	1		
	Provide auto-sensor controlled lighting in conjunction with daylighting strategy for all perimeter zones and daylight areas, including external corridors/compounds, common areas, porch etc.	1		
	Provide motion or occupancy sensors or equivalent to complement lighting zoning equivalent to at least 25% NLA. For guestroom, master switch or access card switch or equiv to switch off all lights, fan, tv and airconditioning when room is not occupied will qualify as occupancy sensor.	1		
EE3	ELECTRICAL SUB-METERING			
	Monitor energy consumption of key building services as well as major Resort facilities:-		2	
	Provide sub-metering for all energy uses ≥ 100kVa and demonstrate suitability of metering for energy monitoring and improvement. (There shall be a minimum of 3 sub-meters for the 3 biggest energy components).	2		
EE4	RENEWABLE ENERGY			
	Encourage use of renewable energy:-		5	
	Where 0.25 % or 2 kWp (PV or equiv) whichever is the greater, of the total electricity consumption is generated by renewable energy, OR	1		
	Where 0.5 % or 5 kWp (PV or equiv) whichever is the greater, of the total electricity consumption is generated by renewable energy, OR	2		
	Where 1.0 % or 10 kWp (PV or equiv) whichever is the greater, of the total electricity consumption is generated by renewable energy, OR	3		
	Where 1.5 % or 20 kWp (PV or equiv) whichever is the greater, of the total electricity consumption is generated by renewable energy, OR	4		
	Where 2.0 % or 40 kWp (PV or equiv) whichever is the greater, of the total electricity consumption is generated by renewable energy.	5		
EE5	ADVANCED OR IMPROVED EE PERFORMANCE			
	l) Exceed Energy Efficiency (EE) performance better than the baseline minimum to reduce energy consumption in the building. Achieve Building Energy Intensity (BEI) as defined by GBI for the following corresponding credit points. The default operating hours for Resort is 24/7. Non-electricity fuel energy is excluded in the BEI calculation.		15	
	BEI ≤ 245, OR	2		
	BEI ≤ 230, OR	3		
	BEI ≤ 212, OR	5		
	BEI ≤ 196, OR	8		
	BEI ≤ 181, OR	10		
	BEI ≤ 165, OR	12		
	BEI ≤ 148	15		

Continued on next page >>

GREEN BUILDING INDEX ASSESSMENT CRITERIA FOR NREB: RESORT

ITEM	AREA OF ASSESSMENT	DETAIL POINTS ALLOCATED	MAX POINTS	SCORE
DESIGN & PERFORMANCE				
EE5	ADVANCED OR IMPROVED EE PERFORMANCE			
	<p><i>OR</i></p> <p>II) Demonstrate Energy savings over the last 3 years from Existing Building historical BEI baseline, to improve by:</p>		15	
	≥ 20% AND with resultant BEI ≤ 327	2		
	≥ 25% AND with resultant BEI ≤ 276	3		
	≥ 30% AND with resultant BEI ≤ 245	5		
	≥ 40% AND with resultant BEI ≤ 230	8		
	≥ 50% AND with resultant BEI ≤ 212	10		
	≥ 60% AND with resultant BEI ≤ 196	12		
	≥ 70% AND with resultant BEI ≤ 181	15		
COMMISSIONING				
EE6	ENHANCED COMMISSIONING/RE-COMMISSIONING/RETRO COMMISSIONING OF BUILDING ENERGY SYSTEMS			
	<p>Ensure building's energy related systems are properly commissioned so as to realise their full potential. Appoint a GBI recognised Commissioning Specialist (CxS) to perform the commissioning for all the building's energy related systems in accordance with ASHRAE Commissioning Guideline or other GBI approved equivalent standard by:-</p> <p>a) Implement improvements to ensure building's major energy using systems are repaired, operated and maintained effectively to optimize energy performance.</p> <p>b) Develop a commissioning or ongoing commissioning plan for the building's major energy-using systems.</p> <p>c) Provide training for management staff to build awareness and skills in a broad range of sustainable building operations topics, including energy efficiency and building, equipment and systems operations and maintenance.</p> <p>d) Update the building operating plan as necessary to reflect any changes in the occupancy schedule, equipment runtime schedule, design set points and lighting levels.</p>	4	4	
EE7	ON-GOING POST OCCUPANCY COMMISSIONING			
	Carry out post occupancy commissioning for all areas where fit-out changes are undertaken.		2	
	a) Professional Engineer shall review all fit-out plans to ensure original design intent is not compromised and sign off the completed works.	1		
	b) CxS shall carry out re-commissioning of the building's energy related systems to verify that their performance is sustained in conjunction with the completed fit-outs.	1		
MONITORING, IMPROVEMENT & MAINTENANCE				
EE8	EE MONITORING & IMPROVEMENT			
	1. Use Energy Management System (or have a dedicated Energy Management Team) to monitor and analyse energy consumption including reading of sub-meters.	1	2	
	2. Fully commission and activate Maximum Demand Limiting programme (where EMS is not provided and air-conditioned area is < 4,000m ² , the dedicated Energy Management Team to demonstrate EE operational strategy), AND	1		
	Compile, summarise and submit BEI, Fuel and Water Consumption of the building to GBI on an annual basis during the 3-years validity period or earlier whenever requested by GBI. Submissions shall include monthly energy and water bills.			
EE9	SUSTAINABLE MAINTENANCE			
	Ensure the building's energy related systems will continue to perform as intended with proper and sustainable maintenance:-		3	
	a) At least 75% of permanent building maintenance team to participate in the commissioning of all building energy services.	1		
	b) Provide for a designated building maintenance office that is fully equipped with facilities (including tools and instrumentation) and inventory storage,	1		
	c) Provide evidence of documented plan for at least 3-year facility maintenance and preventive maintenance budget (inclusive of staffing and outsourced contracts).	1		
EE SUB-TOTAL		38	38	0

2

INDOOR ENVIRONMENTAL QUALITY (EQ)

AIR QUALITY | THERMAL COMFORT | LIGHTING, VISUAL & ACOUSTIC COMFORT | VERIFICATION

16 POINTS

ITEM	AREA OF ASSESSMENT	DETAIL POINTS ALLOCATED	MAX POINTS	SCORE
AIR QUALITY				
EQ1	MINIMUM IAQ PERFORMANCE			
	Establish minimum indoor air quality (IAQ) performance to enhance indoor air quality in building, thus contributing to the comfort and well-being of the occupants:-		1	
	Meet the minimum requirements of ventilation rate in ASHRAE 62.1 or the local building code whichever is the more stringent.	1		
EQ2	ENVIRONMENTAL TOBACCO SMOKE (ETS) CONTROL			
	Minimize exposure of building occupants, indoor surfaces, and ventilation air distribution systems to Environmental Tobacco Smoke (ETS):-		1	
	Prohibit smoking in all spaces provided with air-conditioning and locate any exterior designated smoking areas away from entries, outdoor air intakes and operable windows.	1		
EQ3	INDOOR AIR POLLUTANTS			
	Reduce detrimental impact on occupant health from finishes that emit internal air pollutants:		2	
	Use low VOC paint and coating throughout the building. Paints and Coatings to comply with requirements specified in international labelling schemes recognized by GBI, AND	1		
	Use low VOC carpet or flooring throughout the building. Carpets to comply with requirements specified in international labelling schemes recognized by GBI. Other types of flooring to comply with requirements under FloorScore developed by Science Certification System or equivalent, AND			
	Use low VOC adhesive and sealant or no adhesive or sealant used.			
	Use products with no added urea formaldehyde. These include:	1		
	1) Composite wood and agrifiber products defined as: particleboard, medium density fiberboard (MDF) plywood, wheatboard, strawboard, panel substrates and door cores, AND			
	2) Laminating adhesives used to fabricate on-site and shop-applied composite wood and agrifiber assemblies, AND			
	3) Insulation foam, AND			
	4) Draperies			
EQ4	MOULD PREVENTION			
	Design system(s) which reduce the risk of mould growth and its associated detrimental impact on occupant health:		1	
	Where it is demonstrated that the mechanical air-conditioned ventilation system will maintain a positive indoor air pressure relative to the exterior and can actively control indoor air humidity to be no more than 70% RH without the use of active control that will consume additional energy.			
	Ensure that excessive moisture in building is controlled during the retrofit Design, Construction and Operation stages by the consideration and the control of the following:			
	1) Rainwater leakage through roof and walls	1		
	2) Infiltration of moist air			
	3) Diffusion of moisture through walls, roof and floors			
	4) Groundwater intrusion into basements and crawl spaces through walls and floors			
	5) Leaking or burst pipes			
	6) Indoor moisture sources			
	7) Construction moisture, OR			
	The building is fully naturally ventilated			

Continued on next page >>

GREEN BUILDING INDEX ASSESSMENT CRITERIA FOR NREB: RESORT

ITEM	AREA OF ASSESSMENT	DETAIL POINTS ALLOCATED	MAX POINTS	SCORE
THERMAL COMFORT				
EQ5	AIR MOVEMENT FOR COMFORT			
	Provide air movement for indoor comfort and to reduce airconditioning use in guestrooms:- For guestrooms, provide ceiling fan and contact switch at balcony door/window to switch off airconditioner unit when relevant door/window is opened to prevent wastage of conditioned air.	1	1	
EQ6	THERMAL COMFORT: CONTROLLABILITY OF SYSTEMS			
	Provide a high level of thermal comfort system control by individual occupants or by specific groups in multi-occupant spaces to promote the productivity, comfort and well-being of building occupants:- Provide individual comfort controls for ≥ 50% of the building occupants to enable adjustments to suit individual task needs and preferences. AND Provide comfort system controls for all shared multi-occupant spaces to enable adjustments to suit group needs and preferences. <i>Conditions for thermal comfort include the primary factors of air temperature, radiant temperature, air speed and humidity. Comfort system control for this purpose is defined as the provision of control over at least one of these primary factors in the occupants' local environment.</i>	2	2	
LIGHTING, VISUAL & ACOUSTIC COMFORT				
EQ7	DAYLIGHTING			
	Provide good levels of daylighting for building occupants:- Demonstrate that ≥ 30% of Back-of-the-House (BOTH) and common areas have a daylight factor in the range of 1.0 – 3.5% as measured at the working plane, 800mm from floor level, OR Demonstrate that ≥ 50% of BOTH and common areas have a daylight factor in the range of 1.0 – 3.5% as measured at the working plane, 800mm from floor level.	1 2	2	
EQ8	ELECTRIC LIGHTING LEVELS			
	Baseline building lighting not to be over designed:- Demonstrate that lighting designs for different spaces of the building maintain luminance levels of no more than specified in MS1525 for 90% of NLA.	1	1	
EQ9	HIGH FREQUENCY BALLASTS			
	Increase workplace amenity by avoiding low frequency flicker that may be associated with fluorescent lighting:- Install high frequency ballasts for at least 90% of all fluorescent luminaires used.	1	1	
EQ10	INTERNAL NOISE LEVELS			
	Maintain internal noise levels at an appropriate level. Demonstrate that 90% of the NLA do not exceed the following ambient internal noise levels:- Within the entire baseline building general office, space noise from the building services does not exceed 40dB(A)eq. OR Within the baseline building office space, the sound level does not exceed 45dB(A)eq for open plan and not exceed 40dB(A)eq for closed offices. <i>Note that internal noise level thresholds for areas other than office space shall not exceed values stipulated in ASHRAE Standard or other GBI approved Standards, Code of Practice or Design Guides; e.g. CIBSE Guide.</i>	1	1	

Continued on next page >>

GREEN BUILDING INDEX ASSESSMENT CRITERIA FOR NREB: RESORT

ITEM	AREA OF ASSESSMENT	DETAIL POINTS ALLOCATED	MAX POINTS	SCORE
VERIFICATION				
EQ11	IAQ BEFORE/DURING OCCUPANCY			
	<p>Reduce indoor air quality problems resulting from the construction process (or inherent conditions) in order to improve and sustain the comfort and well-being of building occupants. Develop and implement an Indoor Air Quality (IAQ) Management Plan to effect this requirement as follows:-</p> <p>a) Perform a building flush out by supplying outdoor air to provide not less than 10 airchanges/hour for at least 30 minutes operation and continuous minimum 1 ACH for the next 14 days.</p> <p>OR</p> <p>b) If low VOC materials and low formaldehyde composite wood are used, then building flush out can be performed by supplying outdoor air to provide not less than 10 airchanges/hour for at least 15 minutes operation or not less than 6 airchanges/hour for at least 30 minutes operation and continuous 1ACH for the next 7 days.</p> <p>OR</p> <p>c) Conduct IAQ testing to demonstrate maximum concentrations for pollutants are not exceeded according to the Indoor Air Quality Code of Malaysia.</p>	1	1	
EQ12	OCCUPANCY COMFORT SURVEY: VERIFICATION			
	<p>Provide for the assessment of comfort of the building occupants:-</p> <p>Conduct an occupancy comfort survey of building occupants. This survey should collect anonymous responses about thermal comfort, visual comfort and acoustic comfort in a building. It should include an assessment of overall satisfaction with thermal, visual and acoustic performance and identification of thermal-related, visual-related and acoustic-related problems.</p> <p>AND</p> <p>Develop a plan for corrective action if the survey results indicate that more than 20% of occupants are dissatisfied with the overall comfort in the building. This plan should include measurement of relevant environmental variables in problem areas. <i>The relevant environmental variables include 1) Temperature, relative humidity, air speed and mean radiant temperature, 2) Lighting level and glare problem, 3) Background noise level, 4) Odour problem, CO₂ level, VOCs, and particulate concentration.</i></p>	2	2	
EQ SUB-TOTAL		16	16	0

3

SUSTAINABLE SITE PLANNING & MANAGEMENT (SM)

FACILITY MANAGEMENT | TRANSPORTATION | REDUCE HEAT ISLAND EFFECT

10 POINTS

ITEM	AREA OF ASSESSMENT	DETAIL POINTS ALLOCATED	MAX POINTS	SCORE
FACILITY MANAGEMENT				
SM1	GBI RATED DESIGN & CONSTRUCTION			
	If the building has been previously GBI (or other GBI approved Green Rating system) rated under any category, OR within the last 12 months a comprehensive Energy Efficiency Audit has been conducted.	1	1	
SM2	BUILDING EXTERIOR MANAGEMENT			
	Employ environmentally sensitive building exterior management plan to reduce pollution.	1	1	
	Use environmentally non-polluting methods and chemicals for cleaning of building exterior including maintenance equipment, chemicals, paint and sealants.			
SM3	INTEGRATED PEST MANAGEMENT, EROSION CONTROL & LANDSCAPE MGT			
	Employ environmentally sensitive management to preserve the site's natural components. Minimise harmful chemical use, energy waste, water waste, air pollution, solid waste and/or chemical runoff such as gasoline and oil. The following operational elements must be addressed:	1	1	
	a) Use of least toxic chemical pesticides, minimum use of chemicals and use only in targeted locations and only for targeted species. Conduct routine inspection and monitoring AND b) Erosion and sedimentation control for ongoing landscape operations including measures that prevent erosion and sedimentation, prevent air pollution from dust or particulate matter and restore eroded areas.			
TRANSPORTATION				
SM4	RESORT GUESTS' TRANSPORTATION - GREEN VEHICLE			
	Use of only green vehicles for guests' transport (e.g. airport/port transfer or transportation hubs) and for movement of guests within the resort (such as electric buggies and trishaws).	1	1	
SM5	STAFF MOBILITY - PROVISION OF GREEN TRANSPORTATION			
	Provide bicycles and/or other forms of non motorised transportation for staff movement within the resort.	1	1	
REDUCE HEAT ISLAND EFFECT				
SM6	GREENERY & ROOF			
	Reduce heat island (thermal gradient difference between developed and undeveloped areas) to minimize impact on microclimate and human and wildlife habitat:-	2	4	
	A) Hardscape & Greenery Application: 1) Provide any combination of the following strategies for 50% of the site hardscape (including sidewalks, courtyards, plazas and parking lots): a) Shade (within 5 years of occupancy); b) Paving materials with a Solar Reflectance Index (SRI) of at least 29; c) Open grid pavement system;			
	B) Roof Application: 1) Use roofing material with a Solar Reflectance Index (SRI) equal to or greater than the value in the table below for a minimum of 75% of the roof surface; OR 2) Install a vegetated roof for at least 50% of the roof area; OR 3) Install high albedo and vegetated roof surfaces that, in combination, meet the following criteria: <i>(Area of SRI Roof / 0.75) + (Area of vegetated roof / 0.5) ≥ Total Roof Area</i> <i>Roof Type Slope SRI</i> <i>Low-Sloped Roof < 2:12 78</i> <i>Steep-Sloped Roof > 2:12 29</i>	2		
SM7	BUILDING USER MANUAL			
	Document Green building design features and strategies for user information and guide to sustain performance during occupancy:-	1	1	
	Provide a Building User Manual which documents passive and active features that should not be downgraded (including housekeeping SOP).			
SM SUB-TOTAL		10	10	0

4

MATERIALS & RESOURCES (MR)

REUSED & RECYCLED MATERIALS | SUSTAINABLE MATERIALS & RESOURCES AND POLICY | WASTE MANAGEMENT | GREEN PRODUCTS

9 POINTS

ITEM	AREA OF ASSESSMENT	DETAIL POINTS ALLOCATED	MAX POINTS	SCORE
REUSED AND RECYCLED MATERIALS				
MR1	MATERIALS REUSE AND SELECTION			
	Reuse building materials and products to reduce demand for virgin materials and reduce creation of waste. This serves to reduce environmental impact associated with extraction and processing of virgin resources. Integrate building design and its buildability with selection of reused building materials, taking into account their embodied energy, durability, carbon content and life cycle costs:-		1	
	Where reused products/materials constitutes $\geq 20\%$ of the project's total retrofit material cost value.	1		
MR2	RECYCLED CONTENT MATERIALS			
	Increase demand for building products that incorporate recycled content materials in their production:- <i>(Recycled content shall be defined in accordance with the International Organization of Standards Document)</i>		1	
	Where use of materials with recycled content is such that the sum of post-consumer recycled plus one-half of the pre-consumer content constitutes $\geq 20\%$ (based on cost) of project's total retrofit material cost value.	1		
SUSTAINABLE MATERIALS & RESOURCES AND POLICY				
MR3	SUSTAINABLE TIMBER			
	Encourage environmentally responsible forest management:-		1	
	Where $\geq 75\%$ of wood-based materials and products used in the retrofit works are certified. <i>These components include, but are not limited to, structural framing and general dimensional framing, flooring, sub-flooring, wood doors and finishes. To include wood materials permanently installed and also temporarily purchased for the project. Compliance with Malaysian Timber Certification Scheme or Forest Stewardship Council requirements.</i>	1		
MR4	SUSTAINABLE PURCHASING POLICY			
	Develop a Sustainable Purchasing policy that must cover product purchases within the building and management's control.	1	1	
WASTE MANAGEMENT				
MR5	STORAGE, COLLECTION & DISPOSAL OF RECYCLABLES			
	Facilitate reduction of waste generated during retrofit construction and during building occupancy that is hauled and disposed of in landfills:-		3	
	Provide recycling facilities/infrastructure for sorting and separate collection of recyclable waste for recycling (consumables - glass, paper, metal, equipment, addition & alteration construction wastes).	1		
	Promote and encourage waste minimization and recycling among staff, guests and visitors through various avenues.	1		
	Promote waste sorting, collecting, quantifying, monitoring and recycling of a large range of waste generated in-house.	1		
GREEN PRODUCTS				
MR6	REFRIGERANTS & CLEAN AGENTS			
	Use environmentally-friendly Refrigerants and Fire Suppression Clean Agents exceeding Malaysia's commitment to the Montreal & Kyoto protocols:-		2	
	Use zero Ozone Depleting Potential (ODP) products: non-CFC and non-HCFC refrigerants AND fire suppression clean agents;	1		
	Use non-synthetic (natural) refrigerants AND fire suppression clean agents with zero ODP and negligible Global Warming Potential of ≤ 10 .	1		
MR SUB-TOTAL		9	9	0

5

WATER EFFICIENCY (WE)

WATER HARVESTING & RECYCLING | INCREASED EFFICIENCY

14 POINTS

ITEM	AREA OF ASSESSMENT	DETAIL POINTS ALLOCATED	MAX POINTS	SCORE
WATER HARVESTING & RECYCLING				
WE1	RAINWATER HARVESTING			
	Encourage rainwater harvesting that will lead to reduction in potable water consumption:-		4	
	Rainwater harvesting that leads to ≥5% reduction in potable water consumption, OR	1		
	Rainwater harvesting that leads to ≥15% reduction in potable water consumption, OR	2		
	Rainwater harvesting that leads to ≥30% reduction in potable water consumption, OR	3		
	Rainwater harvesting that leads to ≥50% reduction in potable water consumption.	4		
WE2	WATER RECYCLING			
	Encourage water recycling that will lead to reduction in potable water consumption:-		3	
	Treat and recycle ≥10% wastewater leading to reduction in potable water consumption, OR	1		
	Treat and recycle ≥30% wastewater leading to reduction in potable water consumption, OR	2		
	Treat and recycle ≥50% wastewater leading to reduction in potable water consumption.	3		
INCREASED EFFICIENCY				
WE3	WATER EFFICIENT - IRRIGATION/LANDSCAPING			
	Reduce potable water consumption for landscape irrigation by:		2	
	a) 50%	1		
	b) 100%	2		
WE4	WATER EFFICIENT FITTINGS			
	Encourage reduction in potable water consumption through use of efficient devices (including faucets, washing equipment, etc.):-		3	
	I) With reference to Utility calculations;			
	a) Reduce annual potable water consumption by ≥20%, OR	1		
	b) Reduce annual potable water consumption by ≥30%, OR	2		
	c) Reduce annual potable water consumption by ≥50%	3		
	OR			
	II) From existing 3-year average water consumption record, reduce annual potable water use by:			
	a) ≥ 20%	1		
	b) ≥ 30%	2		
	c) ≥ 50%	3		
WE5	METERING & LEAK DETECTION SYSTEM			
	Encourage the design of systems that monitors and manages water consumption:-		2	
	Use of sub-meters to monitor and manage major water usage for cooling towers, irrigation, kitchens and tenancy use.	1		
	Link all water sub-meters to EMS or have a dedicated Energy Management Team to facilitate early detection of water leakage.	1		
WE SUB-TOTAL		14	14	0

6

INNOVATION (IN)

INNOVATION & ENVIRONMENTAL INITIATIVES | GREEN BUILDING INDEX FACILITATOR

13 POINTS

ITEM	AREA OF ASSESSMENT	DETAIL POINTS ALLOCATED	MAX POINTS	SCORE
IN1	INNOVATION & ENVIRONMENTAL INITIATIVES			
	<p>Provide design team and project the opportunity to be awarded points for exceptional performance above the requirements set by GBI rating system:-</p> <p>1 point for each approved innovation and environmental design initiative up to a maximum of 12 points, such as (refer to GBI website for updates and details);</p> <ul style="list-style-type: none"> • Condensate water recovery (accounting for at least 50% of total AHUs/FCUs) for use e.g., as cooling tower make-up water etc; • Solar thermal technology / Solar Thermal Cooling (generating at least 10% of total required capacity); • Innovative Kitchen Grease & Waste Disposal; • Educational Sorting centre for recycleables; • Beach Erosion Maintenance; • Rehabilitation of unsuitable sandy soil for greenery; • Environmental activities promotion; • Staff eco-awareness training programmes; • Environmental effluent control; • Use of eco-friendly products (bio-degradable soap, shampoo and cleaning agents) throughout resort; • ISO14001 practice with dedicated Sustainable Team; • Solar hot water heaters for at least 90% of guestrooms. 	12	12	
IN2	GREEN BUILDING INDEX FACILITATOR			
	<p>To support and encourage the integration required for Green Building Index rated buildings and to streamline the application and certification process:-</p> <p>Engage the services of a Green Building Index Facilitator to assist in obtaining Green Building Index certification.</p>	1	1	
IN SUB-TOTAL		13	13	0